

Terowax

Solvent-Based Paint Renovator
and High-Gloss Polish

Basis: Hard Waxes

Issue: 2000-04-10

Product Description

Terowax is a solvent-based paint renovator with a special combination of hard waxes (carnauba wax), high-gloss silicones and polishing agents. The material can also be used on wet paintwork.

Application Areas

Terowax is especially useful for renovating the paintwork of used cars where the paint has suffered medium to severe weathering.

Terowax cleans, polishes and protects car paintwork in one operation. It removes dirt which cannot be removed by thorough washing, it dissolves tar splashes, removes oil and insect residues and also removes small particles of surface rust.

Technical Data

Colour:	light blue
Odour:	smells of wax and of petrol
Consistency:	liquid
Density:	approx. 0.95 g/cm ³
Solids:	approx. 20 %
Viscosity (DIN 53211, 4 mm):	approx. 50 s
pH value:	approx. 9.3
Application temperature:	15°C to 25°C

Preliminary remark

Prior to application it is necessary to read the Safety Data Sheet for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

The vehicle should first be thoroughly washed and dried thereafter. Terowax can also be applied to wet paintwork, but cleaning is more effective on dry paintwork. Shake the container well before use. Terowax should be applied with a soft cloth, using light pressure and rubbing with a circular motion. After the product has dried, polish with wadding. Do not use Terowax in direct sunlight or on hot paintwork.

Storage

Frost-sensitive	no
Recommended storage temp.	10°C to 20°C
Shelf-life	12 months

Packaging

Can	1 l	Art.-No. 100.30 C (D/GB/F/NL)
Can	5 l	Art.-No. 138.71 C (D/GB/F/NL)
Can	1 l	Art.-No. 183.40 K (E/P/I/GR)

**Hazard Indications/
Safety Recommendations/
Transport Regulations**

see Safety Data Sheet

Important

The above data, particularly the recommendations for application and use of our products are based on our knowledge and experience. Due to different materials and conditions of application which are beyond our knowledge and control we recommend strongly to carry out sufficient tests in order to ensure that our products are suitable for the intended processes and applications. Except for wilful acts any liability based on such recommendations or any oral advice is hereby expressly excluded.

This Technical Data Sheet supersedes all previous editions.

Henkel Teroson GmbH D-69112 Heidelberg
Telefon: +49 6221 704-0 Telefax: +49 6221 704-698